

# HIKOL PRIMA 5W20 SP GF-6



High Performance – Fully Synthetic Engine Oil

## Product Description

Hikol Prima 5W20 SP GF-6 is an advanced technology engine oil blended in high performance synthetic base stocks fortified with precisely balanced additive system, specifically formulated to help deliver high level of performance and outstanding protection during long service intervals. to provide very high level of engine protection and performance. It is suitable for higher mileage gasoline and diesel fueled automobiles and light duty trucks requiring an API SP specification, where very high viscosity index oils are preferred to provide longer oil drain intervals in modern engines. It provides maximum protection in engines operating under severe conditions, including high-performance turbo-charged, supercharged gasoline and certain diesel multi-valve fuel injected systems.

## Features & Benefits

- Excellent fuel economy & easy cold starts due to extreme fluidity at low temperatures.
- High resistant oil film even at high engine operating temperatures.
- Advanced additive technology, reduces sludge formation which improves engine cleanliness.
- Excellent oxidation & thermal stability, helps in extending oil drain intervals.
- Outstanding engine protection, helps maintain longer engine life and greater compatibility with engine seals.

## Specifications

Hikol Prima 5W20 SP GF-6 meets or exceeds the following International and Builder specifications:

- API SP, SM, SL, SJ
- ILSAC GF-6
- Ford WSS-M2C945-A/WSS-M2C930-A
- General Motors dexos1, GEN - 2

## Application

Hikol Prima 5W20 SP GF-6 series is suitable for use in the following:

- Passenger cars, SUVs, light trucks and vans.
- Suitable for all types of modern vehicles, including high-performance turbo-charged, supercharged gasoline multi-valve fuel injected engines
- Excluded service includes - commercial and racing applications, frequent towing or hauling, extremely dusty or dirty conditions or excessive idling.

## Typical Characteristics

Hikol Prima 5W20	Test Method	Units	5W-20
Density @ 15 °C	ASTM D 4052	gm/cc	0.848
Viscosity @ 100 °C	ASTM D 445	cSt	8.9
Viscosity @ 40 °C	ASTM D 445	cSt	49.5
Viscosity Index	ASTM D 2270	-	161
Pour Point	ASTM D 97	°C	-39
Flash Point (COC)	ASTM D 92	°C	215
Total Base Number	ASTM D 2896	mg KOH/g	8.0
Phosphorous	ASTM D 4951	% wt	0.078
CCS Viscosity	ASTM D 5293	cP	4560 @ -30 °C

\*The above figures are typical of blends with normal production tolerance and do not constitute a specification.

For further information, please contact; [info@hikelube.com](mailto:info@hikelube.com)  
[www.hikelube.com](http://www.hikelube.com)

Powered by HIKE Company Madrid –Spain  
Revision 3: December,2021

