

# Hike Prima 15W40 SN

## Fully Synthetic High-Performance Formulation



### Product Description

Hike Prima 15W40 SN is designed with semi-synthetic base stocks and advanced technology additive system to provide very high level of engine protection and performance. It works harder than other conventional motor oils by continuously preventing dirt and sludge build-up and reduces engine noise. This product meets the requirements of most car manufacturers and is suitable for standard services. This is a very high-quality mineral oil with proven performance. It has been upgraded to meet and exceed ACEA A3/B4. It is suitable for most 4-stroke gasoline and diesel cars as well as light trucks.

### Features & Benefits

- Improved fuel economy & easy cold starts due to good fluidity at low temperatures.
- High resistant oil film even at high engine operating temperatures.
- Excellent detergency and dispersancy, reduces sludge formation which improves engine cleanliness.
- Excellent oxidation & thermal stability, helps in extending oil drain intervals.
- Superior wear protection for greater engine reliability and performance.

### Specifications

**Hike Prima 15W40 SN meets or exceeds following International and Builder specifications:**

- API SN, CF
- ACEA A3/B3, A3/B4
- MB 229.1
- VW 501.01
- FIAT 9.55535 D2/G2
- PSA B71 2295
- VW 505.00

### Application

Hike Prima 15W40 SN is suitable for use in GM, Ford, BMW, VW, Audi and Mercedes Benz.

- Automotive gasoline and diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Moderate duty LPG vehicles.
- Suitable for all petrol engines with multi-valve & turbo types and with or without catalytic converter.
- Naturally aspirated or turbo-charged diesel engines in cars and light vans.
- Fuel injected or indirect injection diesel engines fitted with blow-by recirculation systems.

### Typical Characteristics

Hike Prima 15W40 SN	Test Method	Units	15W-40
Density @ 15 °C	ASTM D 4052	gm/cc	0.878
Viscosity @ 100 °C	ASTM D 445	cSt	14.30
Viscosity @ 40 °C	ASTM D 445	cSt	100
Viscosity Index	ASTM D 2270	-	147
Pour Point	ASTM D 97	°C	-33
Flash Point (COC)	ASTM D 92	°C	230
Total Base Number	ASTM D 2896	mg KOH/g	8.2
Phosphorous	ASTM D 4951	% wt	0.1
CCS Viscosity	ASTM D 5293	cP	5600 @ -20 °C

\* The above figures are typical of blends with normal production tolerance and do not constitute a specification.

For further information , please contact : [info@hikelube.com](mailto:info@hikelube.com)

[www.hikelube.com](http://www.hikelube.com)

Powered by HIKE LUBE, S.L  
de la CASTELLANA,194-28046 Madrid- Spain

Revision 4: December,2021

