

# Hike HD SERIES

## Mono-grade Diesel Engine Oils



### Product Description

HIKE ULTRA HD 60 CF-4 is a range of diesel engine oils formulated with high quality base stocks and selected additives to ensure optimum performance and protection for diesel engines requiring an API CF specification. Suitable for heavy duty, high output diesel engines where monograde oils are specified. It provides excellent protection in engines, against high temperature piston deposits, wear, corrosion and foaming under severe operating conditions.

### Features & Benefits

- Excellent resistance to shearing at extreme operating conditions and retains its lubrication film.
- Good oxidation & thermal stability reduces sludge build up and keeps the engine cleaner.
- Outstanding wear protection to extend engine efficiency and service life.
- Reduced oil consumption at high operating engine temperatures.
- Improved resistance to deposit formation helps keep engine clean.
- High TBN reserves provide improved acid neutralization and corrosion protection, especially in old heavy duty diesel engines.

### Specifications

**HIKE ULTRA HD 60 CF-4 range meets or exceeds following International and Builder specifications:**

- API CF, CD, SF
- ACEA E2
- Mercedes Benz 228.0
- MAN 270
- MTU Type-1
- Caterpillar TO-2

### Application

- Suitable for use in heavy duty 4-stroke turbocharged and naturally aspirated diesel engines.
- It can be used in both On-highway light and heavy duty trucks & construction and mining equipment, where high or low sulfur diesel is used.
- Suitable for certain stationary equipment, such as pumps that run continuously under steady state conditions.

### Typical Characteristics

| SAE 60             | Test Method | Units    | 60     |
|--------------------|-------------|----------|--------|
| Density @ 15 °C    | ASTM D 4052 | gm/cc    | 0.8940 |
| Viscosity @ 100 °C | ASTM D 445  | cSt      | 24.4   |
| Viscosity @ 40 °C  | ASTM D 445  | cSt      | 261.2  |
| Viscosity Index    | ASTM D 2270 | -        | 118    |
| Pour Point         | ASTM D 97   | °C       | -15    |
| Flash Point (COC)  | ASTM D 92   | °C       | 248    |
| Total Base Number  | ASTM D 2896 | mg KOH/g | 9.3    |

*\*Values are changeable according to production.*

For further information, please contact: [Info@hikelube.com](mailto:Info@hikelube.com)

[www.hikelube.com](http://www.hikelube.com)

Powered by HIKE LUBE, S.L

de la CASTELLANA, 194-28046 Madrid- Spain

Revision 4: December,2021

