

Hikol Prima 20W-50 SL/CF

Multigrade Gasoline and Diesel Engine Oil



Product Description

Hikol Prima 20W-50 SL/CF is designed with high quality base stocks and advanced technology additive system to provide high level of protection and performance. It works harder than other conventional motor oils by continuously preventing dirt and sludge build-up and reduces engine noise.

Features & Benefits

- Superior protection against viscosity and thermal breakdown.
- Excellent detergency and dispersancy.
- Superior sludge protection for greater engine reliability.
- Enhanced wear protection and improved engine cleanliness.

Specifications

Hikol Prima meets or exceeds following International and Builder specifications:

- API SL, SJ,CF
- ACEA A3/B3
- MB Approval 229.1
- VW 505 00

Application

Hikol Prima is suitable for use in following:

- Automotive gasoline and diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Moderate duty LPG vehicles.
- Naturally aspirated or turbo-charged engines.
- Fuel injected or indirect injection diesel engines fitted with blow-by recirculation systems.

Typical Characteristics

Hikol Prima	Test Method	Units	20W-50
Density @ 15 °C	ASTM D 4052	gm/cc	0.890
Viscosity @ 100 °C	ASTM D 445	cSt	20.1
Viscosity @ 40 °C	ASTM D 445	cSt	176
Viscosity Index	ASTM D 2270	-	125
Pour Point	ASTM D 97	°C	-24
Flash Point (COC)	ASTM D 92	°C	236
Total Base Number	ASTM D 2896	mg KOH/g	7.8
Phosphorous	ASTM D 4951	% wt	0.098
CCS Viscosity	ASTM D 5293	cP	7560 @ -15 °C

**The above figures are typical of blends with normal production tolerance and do not constitute a specification.*

For further information, please contact; info@hikelube.com
www.hikelube.com

Powered by HIKE Company Madrid –Spain
Revision 3: December,2021

